

Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Door-Oil Trade name:

Article number: 3060 Clear, 3033 Raw

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available. Application of the substance

/ the mixture Coating compound/ Surface coating/ paint

Paint

1.3 Details of the supplier of the safety data sheet

Osmo Holz und Color GmbH & Co. KG Manufacturer/Supplier:

> Affhüppen Esch 12 D-48231 Warendorf

Germany

Further information

obtainable from: Product safety department

> Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in number:

German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation. Additional information: For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements

Hazard pictograms Void Void Signal word Hazard statements Void

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area. EUH210 Safety data sheet available on request.

Additional information:

2.3 Other hazards Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

(Contd. on page 2)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 1)

Results of PBT and vPvB assessment

PBT:Not applicable.vPvB:Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
EC number: 918-481-9 aliphatic hydrocarbons, C10-C13				
	🕸 Asp. Tox. 1, H304, EUH066			
CAS: 13463-67-7	titanium dioxide - aerodynamic dia meter >10 µm	0-<1%		
EINECS: 236-675-5				

SVHC Not applicable.

Additional information: The content of Titanium dioxide varies according to the colour shade.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for

transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or

label.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and

delayed Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

(Contd. on page 3)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

For safety reasons unsuitable

extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or

mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO) carbon dioxide (CO2)

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

General measures for chemical fires.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

protective equipment and emergency procedures

emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

Wear protective clothing.

For non-emergency

personnel

No action shall be taken involving any personal risk or without suitable training.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental

precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Dispose of the material collected according to regulations.

6.4 Reference to other

sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe

handling

Use only in well ventilated areas.

General protective and

hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and

explosion protection:

No special measures required.

Handling: Even a small sip can lead to life

Even a small sip can lead to life-threatening damage to the lungs. Keep rags

filled with this liquid out of the reach of children.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Not required.

Further information about

storage conditions: Store receptacle in a well ventilated area.7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

TWA Short-term value: 1200 mg/m³

CEFIC-HSPA

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls
Appropriate engineering

controls

Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling

chemicals.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

See Section 7 for information on safe handling.

(Contd. on page 5)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 4)

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Use a properly fitted, air-purifying or air-fed repirator complying with an

approved standard if a risk assessment indicates this is necessary.

Hand protection Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture the penetration time has to be at least 480 minutes

(Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable:

Nitrile rubber, NBR

Eye/face protection

Goggles recommended during refilling

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: According to product specification

Odour: Mild

Odour threshold: Not determined.

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range Undetermined.Flammability Not applicable.

(Contd. on page 6)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 5)

Lower and upper explosion limit

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Flash point: > 60 °C (DIN EN ISO 2719)

Ignition temperature: 240 °C

Decomposition temperature: Not determined.

pH Mixture is non-polar/aprotic.

Viscosity:

Kinematic viscosity at 20 °C >81 s (DIN EN ISO 2431/4mm)

>21 mm²/s (40°C) (calculated)

Dynamic: Not determined.

Solubility

water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure:Not determined.

Density and/or relative density

Density at 20 °C: 0.90 - 1.0 g/cm³ (DIN 51757)

Relative density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Solvent content:

VOC (EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void Flammable gases Void Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void

(Contd. on page 7)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 6)

Substances and mixtures, which emit flammablegases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoidDesensitised explosivesVoid

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous

decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Formation of toxic gases is possible during heating or in case of fire.

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:						
	ons, C10-C13					
Γ	Oral	LD50	>5,000 mg/kg (rat)			
İ	Dermal	LD50	>5,000 mg/kg (rat)			
	Inhalative	LC50 / 4h	>5 mg/l (rat)			
Ī	13463-67-7 titanium dioxide - aerodynamic dia meter >10 μm					
ſ	Oral	LD50	>20,000 mg/kg (rat)			
	Dermal	LD50	>10,000 mg/kg (rabbit)			

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the

degreasing effect of the solvent.

(Contd. on page 8)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 7)

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisationBased on available data, the classification criteria are not met.Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.STOT-single exposureBased on available data, the classification criteria are not met.STOT-repeated exposureBased on available data, the classification criteria are not met.Aspiration hazardBased on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

aliphatic hydrocarbons, C10-C13

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h | >1,000 mg/l (algae) LC50 / 96h | >1,000 mg/l (fish)

12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potentialNo further relevant information available.12.4 Mobility in soilNo further relevant information available.

12.5 Results of PBT and vPvB assessmentPBT: Not applicable.vPvB: Not applicable.

12.6 Endocrine disrupting

propertiesThe product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

(Contd. on page 9)



Revision: 26.07.2022

Printing date 26.07.2022

Version number 4.3 (replaces version 4.2)

Trade name: Door-Oil

(Contd. of page 8)

Disposal must be made according to official regulations.

European waste catalogue 08 01 12 waste paint and varnish other than those mentioned in 08 01 11 15 01 04 metallic packaging

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Recommended cleansing

agents:

Solvent naphtha

Osmo Brush Cleaner and Thinner

SECTION 14: Transport information

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Not applicable		
	* 11		
14.2 UN proper shipping name			
ADR, ADN, IMDG, IATA	Not applicable		
14.3 Transport hazard class(es)			
ADR, ADN, IMDG, IATA			
Class	Not applicable		
14.4 Packing group			
ADR, IMDG, IATA	Not applicable		
14.5 Environmental hazards:			
Marine pollutant:	No		
14.6 Special precautions for user	Not applicable.		
14.7 Maritime transport in bulk according to IMO			
instruments	Not applicable.		
UN "Model Regulation":	Not applicable		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC

Product type: PAINTS AND VARNISHES

• Product subcategory: Interior/exterior trim varnishes and woodstains, including opaque woodstains

· Solvent-borne coatings, Limit value: 400 g/l

VOC: <400 g/l

(Contd. on page 10)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil

(Contd. of page 9)

Directive 2012/18/EU Named dangerous

substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

VOC (EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to

Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method

using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Version number of previous

version: 4.2

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route

(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 11)



Printing date 26.07.2022 Version number 4.3 (replaces version 4.2) Revision: 26.07.2022

Trade name: Door-Oil		
	(Contd. of page 10))
	ELINCS: European List of Notified Chemical Substances	
	CAS: Chemical Abstracts Service (division of the American Chemical Society)	
	VOC: Volatile Organic Compounds (USA, EU)	
	LC50: Lethal concentration, 50 percent	
	LD50: Lethal dose, 50 percent	
	PBT: Persistent, Bioaccumulative and Toxic	
	SVHC: Substances of Very High Concern	
	vPvB: very Persistent and very Bioaccumulative	
	Asp. Tox. 1: Aspiration hazard – Category 1	
Sources	ESIS : European chemical Substances Information System	
	ECHA Portal	
	Safety data sheets from raw material suppliers	
* Data compared to the		
previous version altered.	Additions, Deletions, Revisions	
	Updated according to regulation (EU) 2020/878 amending regulation (EC) No: 1907/2006 (REACH)	

EU -