



POLYX®-OIL CARE AND REPAIR PASTE

Ideal for the maintenance and repair of Polyx®-Oil surfaces!



3080 Clear



1 APPLICATION

Product description:

Oil-wax combination for repairing small damages in all wood surfaces treated with Polyx®-Oil. Osmo Polyx®-Oil Care and Repair Paste is based on natural plant oils and waxes.

Recommended use:

Osmo Polyx®-Oil Care and Repair Paste is ideal for wood in indoor areas, such as furniture surfaces and worktops made of solid wood or laminated wood. Also suitable for all wooden flooring, OSB and cork flooring.

Ingredients:

Based on natural plant oils and waxes, paraffin, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free).

Technical Data:

Specific gravity: 0.88-0.95 g/cm³

Odour: faint/mild, odourless after drying

Flashpoint: ≥ 60 °C, acc. DIN EN ISO 2719

pH value: not required

Storage:

2 years and longer if stored in the closed original can.

Surface Preparation:

Wood surface must be clean and dry. It is sufficient to wipe the surface with a lint-free cloth. Strongly contaminated surfaces can be cleaned with, for example, Osmo Spray Cleaner and rubbed dry. Sand small cracks, larger gaps or holes in wood and, if necessary, patch with Osmo Wood Filler.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:

With a lint-free cloth, apply thinly along the wood grain. Allow to dry for approx. 8-10 hours under good ventilation. If necessary, repeat the application as described above 2-3 times.

Drying time:

Approx. 8-10 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

Note:

Oils enhance the natural colour of wood (permanent wet effect). Applying the product too generously and insufficient ventilation lead to delays in drying. If a higher gloss level is desired, after thoroughly drying apply Osmo Liquid Wax Cleaner thinly and polish when dry.

Caution:

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.



Disposal:

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 12). Only completely emptied cans can be recycled.

3080 Clear

Size:

75 g

The above mentioned information is provided to the best of our knowledge however without any liability.

Colour tone:

Version 09/20