

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

SECTION 1: Identification of the substance or mixture and of the supplier

Other means of identification

Trade name: Osmo TopOil

Article number: 3028 Clear Satin, 3037 White, 3038 Terra, 3039 Graphite, 3058 Clear Matt, 3061 Acacia, 3068 Natural

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance

/ the mixture

Paint

Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany

Further information

obtainable from:

Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

Emergency telephone number:

National Poison Centre: 0800 764 766 (0800 POISON)
Chemcall 24/7 Emergency Response Service: 0800 243 622 (0800 CHEMCALL)
Emergency Services (Fire, Ambulance, Police): Dial 111

Importer

Bailey Wood
Osmo New Zealand 2025 Limited
8011 Christchurch
362 Cashel Street
Neuseeland
E-Mail: info@osmo.co.nz
Telefon: 00649575/9849
Mobil: 00642192/9555

SECTION 2: Hazards identification

Classification of the substance or mixture

Flammable liquids Category 4 H227 Combustible liquid.

Additional information: HSNO Classes: 3.1D

Label elements

Hazard pictograms

Void

Signal word

Warning

Hazard statements

H227 Combustible liquid.

(Contd. on page 2)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 1)

Precautionary statements

P102 Keep out of reach of children.
 P210 Keep away from flames and hot surfaces. No smoking.
 P280 Wear protective gloves / eye protection.
 P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
 P403 Store in a well-ventilated place.
 P501 Dispose of contents/container in accordance with national regulations.

Other hazards

Observe the general safety regulations when handling chemicals.
 Always wear a dust mask when sanding.
 Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly.

Results of PBT and vPvB assessment**PBT:** Not applicable**vPvB:** Not applicable

SECTION 3: Composition/Information on ingredients

Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2	25-50%
EC number: 918-481-9	%	
Aspiration hazard Category 1, H304; Flammable liquids Category 4, H227		

SVHC Not applicable**Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

Description of first aid measures**General information:** Take affected persons out into the fresh air.**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.**After swallowing:** Do NOT induce vomiting.
If symptoms persist consult doctor.
**Most important symptoms
and effects, both acute and
delayed**

No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 2)

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.
General measures for chemical fires.

Additional information

Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Keep away from ignition sources.
Wear protective clothing.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

Methods and material for

containment and cleaning up:

Warm water and cleansing agent
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose of the material collected according to regulations.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 3)

SECTION 7: Handling and storage

Precautions for safe handling Use only in well ventilated areas.
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.

General protective and hygienic measures: Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection: Keep respiratory protective device available.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility: Not required

Further information about storage conditions: Protect from frost.
 Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

Storage class: 10

Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

Exposure controls

Appropriate engineering controls Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures: Do not eat, drink, smoke or sniff while working.

(Contd. on page 5)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 4)

Respiratory protection:

Do not carry product impregnated cleaning cloths in trouser pockets.
See Section 7 for information on safe handling.
Use suitable respiratory protective device only when aerosol or mist is formed.
Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.
Not necessary if room is well-ventilated.

Hand protection

To avoid skin problems reduce the wearing of gloves to the required minimum.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection

Goggles recommended during refilling

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties**General Information**

Colour: According to product specification

Odour: Mild

Melting point/freezing point: Undetermined

Boiling point or initial boiling point and boiling range > 180 °C (> 356 °F) (DIN 51751)

(Contd. on page 6)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 5)

Lower and upper explosion limit

Lower:	0.6 Vol %
Upper:	7.0 Vol %
Flash point:	> 60 °C (> 140 °F) (DIN EN ISO 2719)
Auto-ignition temperature:	240 °C (464 °F)
pH	Not applicable
Viscosity:	
Kinematic viscosity	>21 mm ² /s (40°C) (calculated)
Dynamic at 20 °C (68 °F):	120–180 mPas
Solubility	
water:	Not miscible or difficult to mix.
Vapour pressure:	Not determined
Density and/or relative density	
Density at 20 °C (68 °F):	0.92–0.97 g/cm ³ (7.677–8.095 lbs/gal) (DIN 51757)
Particle characteristics	Not applicable

Other information

Appearance:	
Form:	Viscous
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Combustible liquid.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

(Contd. on page 7)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 6)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

Reactivity	No further relevant information available.
Chemical stability	
Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
Possibility of hazardous reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials:	No further relevant information available.
Hazardous decomposition products:	Carbon monoxide and carbon dioxide Nitrogen oxides (NO _x)
Additional information:	Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly.

SECTION 11: Toxicological information

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 7)

Subacute to chronic toxicity: Based on available data, the classification criteria are not met.

Information on other hazards
Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

Toxicity
Aquatic toxicity:
CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h >1,000 mg/l (algae)

LC50 / 96h >1,000 mg/l (fish)

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment
PBT: Not applicable

vPvB: Not applicable

Endocrine disrupting
properties The product does not contain substances with endocrine disrupting properties.

Other adverse effects
Additional ecological information:
General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

Waste treatment methods
Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

Uncleaned packaging:
Recommendation:

Disposal must be made according to official regulations.

Recommended cleansing
agents:

Water, if necessary together with cleansing agents.

Solvent naphtha

Osmo Brush Cleaner and Thinner

(Contd. on page 9)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 8)

SECTION 14: Transport information

UN number or ID number NZS, ADN, IMDG, IATA	Not applicable
UN proper shipping name NZS, ADN, IMDG, IATA	Not applicable
Transport hazard class(es) NZS, ADN, IMDG, IATA Class	Not applicable
Packing group NZS, IMDG, IATA	Not applicable
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable
Maritime transport in bulk according to IMO instruments	Not applicable
UN "Model Regulation":	Not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

New Zealand Inventory of Chemicals
All ingredients are listed.
HSNO Approval numbers
None of the ingredients is listed.

GHS label elements	The product is classified and labelled according to the Globally Harmonised System (GHS).
Hazard pictograms	Void
Signal word	Warning
Hazard statements	H227 Combustible liquid.
Precautionary statements	P102 Keep out of reach of children. P210 Keep away from flames and hot surfaces. No smoking. P280 Wear protective gloves / eye protection. P370+P378 In case of fire: Use CO ₂ , powder or water spray to extinguish. P403 Store in a well-ventilated place. P501 Dispose of contents/container in accordance with national regulations.

(Contd. on page 10)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 17.1 (replaces version 17.0)

Revision: 08.04.2026

Trade name: Osmo TopOil

(Contd. of page 9)

Chemical safety assessment**Named dangerous****substances - ANNEX I**

None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:ADR: Accord relatif au transport international des marchandises dangereuses par route
(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flammable liquids Category 4: Flammable liquids – Category 4

Aspiration hazard Category 1: Aspiration hazard – Category 1

Sources

ESIS : European chemical Substances Information System

ECHA Portal

Safety data sheets from raw material suppliers

*** Data compared to the
previous version altered.**

Additions, Deletions, Revisions

Updated according to regulation (EU) 2020/878 amending regulation (EC) No:
1907/2006 (REACH)