

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

SECTION 1: Identification of the substance or mixture and of the supplier

Other means of identification

Trade name: **UV-Protection-Oil Tints**

Article number: 420, 1420, 424, 425, 426, 427, 428, 429, 431, 432
& mixed colours

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint
Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany

Further information obtainable from:

Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

Emergency telephone number:

National Poison Centre: 0800 764 766 (0800 POISON)
Chemcall 24/7 Emergency Response Service: 0800 243 622 (0800 CHEMCALL)
Emergency Services (Fire, Ambulance, Police): Dial 111

Importer

Bailey Wood
Osmo New Zealand 2025 Limited
8011 Christchurch
362 Cashel Street
Neuseeland
E-Mail: info@osmo.co.nz
Telefon: 00649575/9849
Mobil: 00642192/9555

SECTION 2: Hazards identification

Classification of the substance or mixture

Flammable liquids Category 4

H227 Combustible liquid.

Hazardous to the aquatic environment chronic Category 3
H412 Harmful to aquatic life with long lasting effects.

Additional information:

HSNO Classes: 3.1D; 9.1C
For the wording of the listed hazard phrases refer to section 16.

Label elements

Hazard pictograms Void

(Contd. on page 2)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 1)

Signal word

Warning

Hazard statements

H227 Combustible liquid.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from flames and hot surfaces. No smoking.

P273 Avoid release to the environment.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with national regulations.

Other hazards

Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly.

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment**PBT:**

Not applicable

vPvB:

Not applicable

SECTION 3: Composition/Information on ingredients

Mixtures**Description:**

Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-48-9 EC number: 918-481-9	aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 % Aspiration hazard Category 1, H304; Flammable liquids Category 4, H227	20-40%
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether Flammable liquids Category 4, H227	10-25%
CAS: 127519-17-9 ELINCS: 407-000-3	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates Hazardous to the aquatic environment chronic Category 2, H411; Acute oral toxicity Category 4, H302	<3%

(Contd. on page 3)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 2)

CAS: 84418-68-8 EINECS: 282-780-4	Neodecanoic acid, zinc salt, basic Hazardous to the aquatic environment acute Category 1, H400; Hazardous to the aquatic environment chronic Category 2, H411; Flammable liquids Category 4, H227	≥0.25–≤1%
CAS: 55406-53-6	3-Iodo-2-propynylbutylcarbamate Acute inhalation toxicity Category 2, H330; Specific target organ toxicity - repeated exposure Category 1, H372; Serious eye damage Category 1, H318; Hazardous to the aquatic environment acute Category 1, H400 (M=10); Hazardous to the aquatic environment chronic Category 1, H410 (M=10); Acute oral toxicity Category 4, H302; Skin sensitisation Category 1, H317	≥0.1–<0.25%

SVHC

Not applicable

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

Description of first aid measures

General information:

Take affected persons out into the fresh air.
Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

After eye contact:

If skin irritation or rash occurs: Get medical advice/attention.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth.
If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Headache
Dizziness

Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

(Contd. on page 4)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 3)

SECTION 5: Fire fighting measures

Extinguishing media
Suitable extinguishing
agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable
extinguishing agents:

For this mixture there are no extinguishing agent restrictions.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)
carbon dioxide (CO₂)

Advice for firefighters
Protective equipment:

Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
General measures for chemical fires.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Keep away from ignition sources.
Wear protective clothing.

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training.

For emergency responders

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

Methods and material for
containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose of the material collected according to regulations.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Warm water and cleansing agent

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 4)

See Section 13 for disposal information.

SECTION 7: Handling and storage

Precautions for safe handling Use only in well ventilated areas.
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.

General protective and hygienic measures: Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection: Keep respiratory protective device available.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Handling: Even a small sip can lead to life-threatening damage to the lungs. Keep rags filled with this liquid out of the reach of children.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility: Not required

Further information about storage conditions: Store receptacle in a well ventilated area.
 Protect from frost.
 Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

Storage class: 10

Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

WES Long-term value: 308 mg/m³, 50 ppm

(Contd. on page 6)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 5)

DNELs**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	36 mg/kgKG/Tag
Dermal	DNEL Verbraucher (Langzeit - systemische Effekte)	121 mg/cm ²
Inhalative	Worker (chronic - Systemic health effec)	308 mg/m ³
	DNEL Verbraucher (Lanzzeit - systemische Effekte)	37.2 mg/m ³

PNECs**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

PNEC sea water	1.9 mg/l
PNEC fresh water	19 mg/l
PNEC sediment (fresh water)	70.2 mg/kg
PNEC sediment (sea water)	7.02 mg/kg
PNEC soil	2.74 mg/kg
PNEC sewage treatment plant	4,168 mg/l
interrupted release	190 mg/l

Additional information: The lists valid during the making were used as basis.
Exposure controls**Appropriate engineering****controls**

Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment**General protective and****hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.
 Immediately remove all soiled and contaminated clothing
 The usual precautionary measures are to be adhered to when handling chemicals.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.
 See Section 7 for information on safe handling.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.
 Not necessary if room is well-ventilated.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.
 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection

Protective gloves

(Contd. on page 7)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 6)

Material of gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties**General Information****Physical state**

Liquid

Colour:

According to product specification

Odour:

Mild

Odour threshold:

Not determined

Melting point/freezing point:

Undetermined

Boiling point or initial boiling point and boiling range

> 180 °C (> 356 °F)

Flammability

Not applicable

Lower and upper explosion limit**Lower:**

0.7 Vol %

Upper:

14.0 Vol %

Flash point: ≥ 63 °C (≥ 145.4 °F) (DIN EN ISO 2719)**Auto-ignition temperature:**

Undetermined

Decomposition temperature:

Not determined

pH

Mixture is non-polar/aprotic.

(Contd. on page 8)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 7)

Viscosity:**Kinematic viscosity at 20 °C (68 °F)**

60–80 s (DIN EN ISO 2431/4 mm)

Dynamic:

Not determined

Solubility**water:**

Fully miscible.

Partition coefficient n-octanol/water (log value)

Not determined

Vapour pressure at 20 °C (68 °F):

0.4 hPa (0.3 mm Hg)

Density and/or relative density**Density at 20 °C (68 °F):**0.9-1.0 g/cm³ (7.511-8.345 lbs/gal) (DIN 51757)**Relative density**

Not determined

Particle characteristics

Not applicable

Other information**Appearance:****Form:**

Fluid

Important information on protection of health and environment, and on safety.**Ignition temperature:**

Product is not selfigniting.

Explosive properties:

Product does not present an explosion hazard.

Solvent content:**VOC (EC)**

<400 g/l

Change in condition**Evaporation rate**

Not determined

Information with regard to physical hazard classes**Explosives**

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Combustible liquid.

Flammable solids

Void

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Void

Pyrophoric solids

Void

Self-heating substances and mixtures

Void

Substances and mixtures, which emit flammable gases in contact with water

Void

Oxidising liquids

Void

Oxidising solids

Void

Organic peroxides

Void

Corrosive to metals

Void

(Contd. on page 9)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 8)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

Reactivity	No further relevant information available.
Chemical stability	
Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
Possibility of hazardous reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials:	No further relevant information available.
Hazardous decomposition products:	Carbon monoxide and carbon dioxide Nitrogen oxides (NO _x) Formation of toxic gases is possible during heating or in case of fire.
Additional information:	Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly.

SECTION 11: Toxicological information

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	72,197 mg/kg (rat)
Inhalative	LC50 / 4h	46.5 mg/l

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat)
		13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)

(Contd. on page 10)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 9)

	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)
CAS: 127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates		
Oral	LD50	2,000 mg/kg (rat)
CAS: 84418-68-8 Neodecanoic acid, zinc salt, basic		
Oral	LD50	>5,000 mg/kg (rat) (Acute Oral Toxicity)
Dermal	LD50	>3,640 mg/kg (rat) (Acute Dermal Toxicity)
	LC50 / 72h	2.05 mg/l (algae)
CAS: 55406-53-6 3-Iodo-2-propynylbutylcarbamate		
Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	0.05 mg/l (ATE)

Primary irritant effect:**Skin corrosion/irritation** Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin****sensitisation** Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**Subacute to chronic toxicity:** Based on available data, the classification criteria are not met.**Information on other hazards****Endocrine disrupting properties**

CAS: 55406-53-6	3-Iodo-2-propynylbutylcarbamate	List II
-----------------	---------------------------------	---------

SECTION 12: Ecological information**Toxicity****Aquatic toxicity:**

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %	
EC50 / 48h	>1,000 mg/l (Daphnia magna)
IC50 / 72h	>1,000 mg/l (algae)
LC50 / 96h	>1,000 mg/l (fish)
CAS: 34590-94-8 Dipropylene glycol monomethyl ether	
EC50 / 48h	70.2 mg/l

(Contd. on page 11)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 10)

EC50/ 72h	1,919 mg/l (Daphnia magna)
LC50 / 96h	>969 mg/l (algae)
	>10,000 mg/l (aquatic vertebrates - in vivo)
	>1,000 mg/l (fish)
LC50 / 48h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
	1,919 mg/l (daphnia)
	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
CAS: 127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates	
EC50 / 48h	3.2 mg/l (Daphnia magna) (24h EC 50 acute immobilisation test)
Bioconceived factor	<3 (Flow-through fish test)
CAS: 84418-68-8 Neodecanoic acid, zinc salt, basic	
IC50/ 3h	5.2 mg/l (activated sludge organism) (Activated Sludge, Respiration Inhibition Test)
LC50 / 96h	0.112 mg/l (fish)
NOEC / 3 days	0.06 mg/l (algae)
CAS: 55406-53-6 3-Iodo-2-propynylbutylcarbamate	
EC50 / 48h	0.16 mg/l (Daphnia magna)
EC50/ 72h	0.022 mg/l (algae)

Persistence and degradability No further relevant information available.**Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Results of PBT and vPvB assessment****PBT:** Not applicable**vPvB:** Not applicable**Endocrine disrupting****properties** For information on endocrine disrupting properties see section 11.**Other adverse effects**

Remark: Harmful to aquatic life with long lasting effects.
Harmful to fish

Behaviour in sewage processing plants:**CAS: 34590-94-8 Dipropylene glycol monomethyl ether**

EC50/ 96h 969 mg/l (algae)

CAS: 55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50/ 96h 0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 12)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 11)

Harmful to aquatic organisms

SECTION 13: Disposal considerations

Waste treatment methods
Recommendation

Do not clean empty packaging before disposal.
 Paint must not be flushed down the drain, not even when cleaning painting tools.
 Consumers: Dispose of paint leftovers at your local household hazardous waste collection point.
 Professionals: Dispose of paint leftovers by contracting a waste management company.
 For information on the prevention of the release of synthetic polymer particles see Section 15

Uncleaned packaging:
Recommendation:

Disposal must be made according to official regulations.

Recommended cleansing
agents:

Solvent naphtha
 Osmo Brush Cleaner and Thinner

SECTION 14: Transport information

UN number or ID number
NZS, ADN, IMDG, IATA

Not applicable

UN proper shipping name
NZS, ADN, IMDG, IATA

Not applicable

Transport hazard class(es)
NZS, ADN, IMDG, IATA
Class

Not applicable

Packing group
NZS, IMDG, IATA

Not applicable

Environmental hazards:
Marine pollutant:

No

Special precautions for user

Not applicable

Maritime transport in bulk according to IMO instruments

Not applicable

(Contd. on page 13)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 12)

UN "Model Regulation":

Not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
New Zealand Inventory of Chemicals

All ingredients are listed.

HSNO Approval numbers

This product is approved under the Surface Coatings and Colourants (Combustible) Group Standard 2020 (HSR002657) and complies with the requirements of the Hazardous Substances (Safety Data Sheets) Notice 2017.

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

Void

Signal word

Warning

Hazard statements

H227 Combustible liquid.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from flames and hot surfaces. No smoking.

P273 Avoid release to the environment.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with national regulations.

Chemical safety assessment
Named dangerous
substances - ANNEX I

None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

(Contd. on page 14)

Safety Data Sheet

in accordance with HSNO

Date of issue: 08.04.2026

Version number 6.1 (replaces version 6.0)

Revision: 08.04.2026

Trade name: UV-Protection-Oil Tints

(Contd. of page 13)

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route
 (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flammable liquids Category 4: Flammable liquids – Category 4
 Acute oral toxicity Category 4: Acute toxicity – Category 4
 Acute inhalation toxicity Category 2: Acute toxicity – Category 2
 Serious eye damage Category 1: Serious eye damage/eye irritation – Category 1
 Skin sensitisation Category 1: Skin sensitisation – Category 1
 Specific target organ toxicity - repeated exposure Category 1: Specific target organ toxicity
 (repeated exposure) – Category 1
 Aspiration hazard Category 1: Aspiration hazard – Category 1
 Hazardous to the aquatic environment acute Category 1: Hazardous to the aquatic environment -
 acute aquatic hazard – Category 1
 Hazardous to the aquatic environment chronic Category 1: Hazardous to the aquatic environment
 - long-term aquatic hazard – Category 1
 Hazardous to the aquatic environment chronic Category 2: Hazardous to the aquatic environment
 - long-term aquatic hazard – Category 2
 Hazardous to the aquatic environment chronic Category 3: Hazardous to the aquatic environment
 - long-term aquatic hazard – Category 3

Sources

ESIS : European chemical Substances Information System
 ECHA Portal
 Safety data sheets from raw material suppliers

*** Data compared to the
 previous version altered.**

Additions, Deletions, Revisions
 Updated according to regulation (EU) 2020/878 amending regulation (EC) No:
 1907/2006 (REACH)